



**United States Steel
SUPER STEEL SIDING®**

40 Year Hail Protection Warranty

PRORATED-TRANSFERABLE-MATERIAL AND LABOR-LIMITED WARRANTY • \$100.00 DEDUCTIBLE

Protection Against Hail Damage for 40 Years

United States Steel Super Steel Siding is warranted by the Manufacturer, Alside, Inc., a wholly-owned subsidiary of United States Steel Corporation, to the Property Owner against damage from hail for a period of Forty (40) Years from date of installation, based upon the Application submitted and subject to the provisions of this Warranty Certificate.

Notice of Claim and Inspection

If it is believed that hail damage has occurred to the United States Steel Super Steel Siding, it is only necessary to file a written claim within the Warranty period, describing the occurrence promptly after discovery of the damage, to: Hail Warranty Services, Alside, Inc., P.O. Box 2010, Akron, Ohio 44309, referring to this Certificate Number and date of issuance. Allow a reasonable time for inspection of the claimed hail damage. No replacement work should be performed without the prior authorization of Alside, Inc. **Material and Labor for Replacement of Hail Damaged Siding Panels***

Remedial Action-Deductible Amount and Prorate

If after inspection, it is found that hail damage has occurred to the United States Steel Super Steel Siding, then the Manufacturer will replace only the hail damaged siding panels on the following basis:

\$100.00 Deductible—Balance 100% Manufacturer Paid During First Three Years

During the Three Year period immediately following date of siding installation, the Property Owner will pay only the first \$100.00 of the cost of material and labor for panel replacement, for each incident of hail damage, as to each building unit, and the Manufacturer will pay the full balance of such material and labor costs for hail damaged siding panel replacement in effect at the time of replacement.

\$100.00 Deductible and Prorated Amount Payable From Fourth Year Through 40th Year

Commencing from the start of the Fourth Year following date of siding installation, the Property Owner will pay the first \$100.00 of the cost of panel replacement. The balance of the cost of material and labor for hail damaged siding panel replacement in excess of \$100.00 will be

prorated between the Property Owner and the Manufacturer on the following basis:

The Manufacturer will assume 92% of such remaining costs of material and labor for replacement of hail damaged siding panels during the fourth year, 8% less than the preceding year for each additional year thereafter through 10th year, and then the Manufacturer agrees to assume 3% less of such remaining costs for each additional year thereafter through the 15th year, 2% less than the preceding year for each additional year thereafter through the 24th year, and thereafter the Manufacturer's liability hereunder from the 25th year shall be 10% of such remaining costs through the 40th year, at the end of which period of time, all liability and obligation of the Manufacturer under this Hail Protection Warranty will cease and terminate.

Other Provisions

This Warranty covers hail damage only and provides such hail protection coverage for United States Steel Super Steel Siding installed on and after November 1, 1978.

All Warranty claims shall be resolved between the Manufacturer and the Property Owner, but the replacement work under this Warranty shall be performed only after authorization by the Manufacturer, Alside, Inc. Manufacturer's obligation under this Warranty may be performed by persons designated and compensated by Manufacturer for that purpose. The \$100.00 payment representing deductible amount and any additional amount due for prorated cost share shall be paid by the Property Owner upon authorization of such panel replacement work. A color variance may occur between the new replacement panels in comparison to the originally installed panels due to weathering exposure and would not be indicative of defective materials.

The original Warranty period shall not be extended by any such replacement of hail damaged siding panels, but after any such replacement the remaining Warranty time period shall continue in effect and be applicable under the terms and conditions of this Hail Protection Warranty.

The Manufacturer reserves the right to change or discontinue any siding style or color at any time during the

Warranty period without notice and to provide a substitute siding replacement of comparable quality and value for the hail damaged siding panels if the siding originally installed is not then available.

Alside, Inc., the Manufacturer, extends to the Property Owner an express Forty (40) Year Limited Warranty for hail damaged siding panels under the provisions of the Federal Warranty Law. The exclusive remedial action provided for the Property Owner hereunder shall be replacement of hail damaged siding panels for the genuine United States Steel Super Steel Siding panels originally installed, less the first \$100.00 cost of material and labor for panel replacement and including applicable proration for the balance of replacement costs, for each incident of hail damage, as to each building unit, under the terms and conditions of this Warranty Certificate.

The Warranty statements contained in this Certificate set forth the only express Hail Protection Warranties of Alside, Inc., and the provisions hereof shall constitute the Property Owner's exclusive remedy for breach of the Warranty given under this Certificate. Any implied warranties imposed by law, such as the implied warranties of merchantability or fitness for a particular purpose are limited in time to the express duration of this Warranty. Alside, Inc., shall not be liable to the Property Owner for incidental or consequential damages for breach of any written or implied warranty on the siding.

Some states do not allow limitations on how long an implied warranty lasts, and some states do not allow the exclusion or limitation of incidental or consequential damages, so the above limitations or exclusions may not apply to you. This Warranty gives you specific legal rights, and you may also have other rights which vary from state to state.

This Warranty is transferable by the original Property Owner to subsequent purchasers of the property provided Alside, Inc., receives notice of transfer of title of the above property within 30 days after the date of the sale. In the event of transfer of the Warranty, the Warranty period shall be 40 years from the original date of this Warranty.

Certificate Number...
H 28316

Issued by Alside, Inc., this 5th day of June, 1982

Manufactured by Alside, Inc.
A Wholly Owned Subsidiary of
United States Steel Corporation
P.O. Box 2010, Akron, Ohio 44309



CERTIFICATE OF TRANSFER FOR 40-YEAR HAIL PROTECTION WARRANTY LIMITED WARRANTY

Complete this card, have signed by both original purchaser and new property owner and returned within 30 days of transfer of house (or building) title, if originally registered.

Date of Transfer _____
 Name of original property owner _____
 Location of house (or building) on which United States Steel Super Steel Siding has been installed:
 Street _____ City _____ State _____ Zip _____
 Date of installation of United States Steel Super Steel Siding _____

This is to certify that the individual named purchased the house (or building) located at address above and is to be protected by Alside 40-Year Material and Labor Hail Protection Warranty.
 Full Name of new Property Owner _____
 Signature of new Property Owner _____

Certificate Number...
H 28316
 I hereby certify that I have transferred title within the past 30 days to individual indicated and relinquish all claims under this warranty.

THE CARE AND MAINTENANCE OF STEEL SIDING

INSTRUCTIONS

Under normal conditions your USS-United States Steel Super Steel Siding will require nothing more than periodic hosing with clear water to remove loose soil. This is particularly important in areas which are not readily accessible to sun and rain.

The finish on your siding is formulated to be self-cleaning. When exposed to the weather, the surface will oxidize at a controlled rate to shed most any surface soil deposited. This chalk film will also serve to retard dirt collection and erosion of the surface which can shorten the service life of your siding. In shaded areas or if your home is located in a high soil collection area, periodic washing may be necessary to prevent build-up of dirt which can become imbedded into the finish. Use a household cleaner such as "Fantastik" available in supermarkets, or "Industro-Clean" available from Amway distributors. Follow label instructions, using a soft rag or sponge. Do not rub vigorously which may create glossy areas over the satin finish. Soft bristle brushes equipped with long extension handles may be used to reach some of the higher areas.

As in any wall cleaning operation, less streaking will result if the siding is washed from bottom to top. It is important that immediately following all washing operations, the entire surface be thoroughly rinsed with fresh water from a garden hose.

For best results, select an overcast cool day (ideal temperature 55° to 75° F) and wash only small (6 ft. x 6 ft.) areas at a time. This should allow the wet cleaning solution to remain in contact with the finish for a period of not less than 3 minutes; then rinse with clear water **before** siding has a chance to dry. Avoid washing siding in direct sunlight, as the cleaning solution will tend to dry rapidly, inhibiting cleaning action and making residue difficult to rinse off.

STUBBORN STAINS

If stubborn stains are encountered, "Fantastik" or "Industro-Clean" may be used at full strength but must be removed by thorough rinsing with fresh water. Heavy soil deposits may not be removable in one application and may require repeated cleaning over some length of time.

CAUTION: DO NOT USE CLEANSERS CONTAINING ABRASIVE PARTICLES, SOLVENT OR AMMONIATED TYPE CLEANERS OR PAINT REMOVER FOR CLEANING YOUR SIDING. THESE MATERIALS MAY SOFTEN OR ACTUALLY REMOVE YOUR SIDING FINISH.

CLIMATIC CONDITIONS

Climatic conditions vary considerably from one locality to the next. In some locales, mildew may be a problem. It appears as black spots occurring on the surface dirt and is usually first detected in areas not subjected to rainfall, such as under eaves and porch enclosures. For removal, prepare a solution as follows and comply to the aforementioned washing and rinsing procedures:

- 1 3 Cup Detergent (Tide, for example)
- 2 3 Cup Trisodium Phosphate (Solaax, for example)
- 1 Or. 5% Sodium Hypochlorite (Clorox, for example)
- 3 Ors. Water

CAUTION: GREATER CONCENTRATIONS MAY CAUSE DAMAGE TO THE SIDING FINISH.

The above information is offered in an effort to be of assistance; however, manufacturer can assume no responsibility for the result.

USS and Alside are registered trademarks.
 © Alside, Inc., 1978 Printed in U.S.A.
 75-2724-01 337



40 Year
Material and Labor
Hail
Protection
Warranty

PRORATED-TRANSFERABLE-MATERIAL AND LABOR*-LIMITED WARRANTY \$100.00 DEDUCTIBLE

ISSUED TO:

Art True (Property Owner)
 918 Kingham (Property Address)
 Cheyenne (City)
 Wyoming 82001 (Zip)
(State)

MANUFACTURED BY ALSIDE, INC.
 A WHOLLY OWNED SUBSIDIARY OF
 UNITED STATES STEEL CORP.

Name _____
 Address _____

Put Stamp here
 The Post Office
 will not deliver
 mail without
 postage

ALSIDE, INC.
 P.O. BOX 2010
 AKRON, OHIO 44309

**ATTENTION:
 HAIL WARRANTY SERVICES**